

Q313 HIGH TEMPERATURE, HIGH SOLIDS, PRESSURE SENSITIVE SPRAY MIST ADHESIVE is a fast tack, high strength adhesive. Q313 is especially formulated for permanent or temporary bonding. Q313 is best effective when both substrates are coated. Q313 can be used on paper, wood, fabrics, metal, plastics and many other surfaces. Q313 has high solids and has a water-resistant bond, quick tack and high temperature resistance. All substrates should be tested for compatibility before using in production. Product should be used and works best at 70°F.

Container Size	20 FLUID OZ.
Product Description	Aerosol Adhesive
Net Weight	14 Ounces
Weight Per Gallon	6.59
Cans Per Case	12
Case Dimensions - Inches	10.875"L X 8.125" W X 9.375" H
Case Weight	15 Pounds
Cases Per Pallet	108
Appearance	Natural/Red
Odor	Pungent
Solvent System	Cyclohexane, Acetone
Propellant	Hydrocarbon Blend
Open Time	10 Minutes
Tack Time	2-4 Minutes
Heat Resistance	Max Temp 200°F
Viscosity	8,000 cps #1 spindle @10 rpm
Solids	25% +/- 3%
Spray Pattern	Mist
VOC %	55%
VOC Compliant for CA & OTC	Yes
Aerosol Flammability Level	Level 3, Flammable
Warranty Period	One Year From Date of Shipment
DOT Proper Shipping Name	Consumer Commodity ORM-D for domestic ground shipment. (See MSDS for additional shipping info)

Office: 678.494.1112 • Fax: 678.494.1113 • 313 Bell Park Drive • Woodstock, GA 30188

Where Quality and Service are Number 1

www.losorea.com • www.qualityaerosols.com