

Q5250 LCF - CONTACT ADHESIVE - FLAMMABLE - BRUSH/ROLL GRADE is a VOC Compliant premium grade, fast drying quick-setting, brushable polychloroprene contact adhesive designed to produce a strong permanent bond when used with a variety of porous and non-porous substrates. Q5250 is recommended for permanent bonding of high pressure laminates to substrates, such as wood, particle board, plywood, etc., and may also be used for making permanent bonds to other compatible non-porous and porous substrates such as rubber, foam and metal. It is recommended that all substrates be tested for compatibility with adhesive before using in production.

Container Size	5 Gallon Pail	55 Gallon Drum
Product Description	Bulk Adhesive	Bulk Adhesive
Net Weight	38 lbs.	426 lbs.
Weight Per Gallon	7.75	7.75
Pails/Drums Per Pallet	36	4
Appearance	Tan/Red	Tan/Red
Odor	Slight Solvent	Slight Solvent
Solvent System	Hexane, Acetone,	Hexane, Acetone,
Open Time	20-30 Minutes	20-30 Minutes
Tack Time	5-10 Minutes	5-10 Minutes
Heat Resistance	200+ F.	200+ F.
Viscosity	1000 cps	1000 cps
Solids	18% +/- 1%	18% +/- 1%
Spray Pattern	N/A	N/A
VOC Grams per Liter	233 g/l	233 g/l
VOC Compliant for CA & OTC	Yes	Yes
Flammability Level	Level 3, Flammable	Level 3, Flammable
Warranty Period	One Year From Date of Shipment	One Year From Date of Shipment
DOT Proper Shipping Name	UN1133/Class 3 domestic ground shipment. (See MSDS for additional shipping info)	UN1133/ Class 3 domestic ground shipment. (See MSDS for additional shipping info)

Office: 678.494.1112 • Fax: 678.494.1113 • 313 Bell Park Drive • Woodstock, GA 30188

Where Quality and Service are Number 1

www.losorea.com • www.qualityaerosols.com