

**Q5500 LWB CONTACT WATER BORNE
 PRODUCT DATA SHEET
 VOC COMPLIANT — ALL STATES**

Q5500 SOLVENT FREE POLYCHLOROPRENE BASED CONTACT SPRAY ADHESIVE is a high shear strength, exceptional tack adhesive. Q5500 is especially formulated for permanently bonding high pressure laminates to various substrates, but is suitable for a variety of applications in the manufactured housing, general construction, recreational vehicle, marine, woodworking, furniture, and many other industries. Do not allow this product to freeze. Shelf life is 6 months. Test product on substrates before using in a production run. Product should be used at room temperature or at least at 70°F.

Container Size	38# DOT 923-933-39 & TC -39M
Product Description	Canister Adhesive
Net Weight	35 Lbs.
Weight Per Gallon	9.18
Cans Per Case	1
Case Dimensions - Inches	12.50"L X 12.50" W X 18.00"H
Case Weight	52
Cases Per Pallet	36
Appearance	Natural or Green
Odor	Pungent
Solvent System	Solvent Free
Propellant	Compressed Gas
Open Time	45-60 minutes
Tack Time	20-30 minutes
Heat Resistance	Max Temp 220°F
Viscosity	8,000cps #1 spindle @10 rpm
Solids	55% +/- 2%
Spray Pattern	Web
VOC %	0 g/l
VOC Compliant for CA & OTC	Yes
Aerosol Flammability Level	Non-Flammable
Warranty Period	Six Months From Date of Shipment
DOT Proper Shipping Name	UN1956/Class 2.2 for domestic ground shipment. (See MSDS for additional shipping info)

Office: 678.494.1112 • Fax: 678.494.1113 • 313 Bell Park Drive • Woodstock, GA 30188

Where Quality and Service are Number 1

www.losorea.com • www.qualityaerosols.com