

**Q5550 LWB CONTACT WATER BORN
 PRODUCT DATA SHEET**

BRUSH/ROLL GRADE - VOC COMPLIANT - ALL STATES

Q5550 SOLVENT FREE POLYCHLOROPRENE BASED CONTACT SPRAY ADHESIVE is a high shear strength, exceptional tack adhesive. Q5550 is especially formulated for permanently bonding high pressure laminates to various substrates, but is suitable for a variety of applications in the manufactured housing, general construction, recreational vehicle, marine, woodworking, furniture, and many other industries. Do not allow this product to freeze. Shelf life is 6 months. Test product on substrates before using in a production run. Product should be used at room temperature or at least at 70°F.

Container Size	5 Gallon Pail	55 Gallon Drum
Product Description	Bulk Adhesive	Bulk Adhesive
Net Weight	35	400
Weight Per Gallon	9.18	9.18
Pails/Drums Per Pallet	36	4
Appearance	Natural/Green	Natural/Green
Odor	Pungent	Pungent
Solvent System	Solvent Free	Solvent Free
Open Time	45-60 Minutes	45-60 Minutes
Tack Time	20-30 Minutes	20-30 Minutes
Heat Resistance	Max Temp 220°F	Max Temp 220°F
Viscosity	8,000 cps #1 spindle @10 rpm	8,000 cps #1 spindle @10 rpm
Solids	55% +/- 2%	55% +/- 2%
Spray Pattern	N/A	N/A
VOC Grams per Liter	0 g/l	0 g/l
VOC Compliant for CA & OTC	Yes	Yes
Flammability Level	Non Flammable	Non Flammable
Warranty Period	Six Months From Date of Shipment	Six Months From Date of Shipment
DOT Proper Shipping Name	UN1956/Class 2.2 domestic ground shipment. (See MSDS for additional shipping info)	UN1956/Class 2.2 domestic ground shipment. (See MSDS for additional shipping info)

Office: 678.494.1112 • Fax: 678.494.1113 • 313 Bell Park Drive • Woodstock, GA 30188

Where Quality and Service are Number 1

www.losorea.com • www.qualityaerosols.com