

Q6200 LPF PRESSURE SENSITIVE FLAMMABLE PRODUCT DATA SHEET VOC COMPLIANT - ALL STATES

Q6200 HIGH SOLIDS, HIGH TEMPERATURE SPRAY ADHESIVE is a fast tack, high shear strength low soak in adhesive. Q6200 is especially formulated to bond fabric, foam, plywood, high density fiberglass, molded fiberglass, metal, most plastic, wood and a variety of other substrates. Q6200 is an excellent choice for temporary or permanent bonds and is also excellent for carpet where strong shear strength and peel strength along with the ability to re-position the substrate is necessary before bonding. Product should be used at room temperature or at least 70°F.

Container Size	20 Fluid oz. Container	11# DOT 923-267 424.7 CU. In.	38# DOT 923-933-39 & TC -39M	177# TC #14761	355# TC 200 Gallon
Product Description	Aerosol Adhesive	Canister Adhesive	Canister Adhesive	Cylinder Adhesive	Cylinder Adhesive
Net Weight	14 Ounces	9 lbs.	30 lbs.	145 lbs.	300 lbs.
Weight Per Gallon	6.5	6.5	6.5	6.5	6.5
Can Per Case	12	1	1	1	1
Case Dimensions - Inches	10.875"L X 8.125" W X 9.375" H	10.00"L X 10.00" W X 17.25" H	12.50"L X 12.50" W X 18.00"H	16" diameter X 49" High	25" diameter X 42" High
Case Weight	14.7 Pounds	17.0 Pounds	44.0 Pounds	214.0 Pounds	447.00 Pounds
Cases Per Pallet	108	60	36	9	4
Appearance	Natural/Green	Natural/Green	Natural/Green	Natural/Green	Natural/Green
Odor	Slight Solvent	Slight Solvent	Slight Solvent	Slight Solvent	Slight Solvent
Solvent System	Hexane, Acetone, Methyl Acetate	Hexane, Acetone, Methyl Acetate	Hexane, Acetone, Methyl Acetate	Hexane, Acetone, Methyl Acetate	Hexane, Acetone, Methyl Acetate
Propellant	Hydrocarbon Blend	Hydrocarbon Blend	Hydrocarbon Blend	Hydrocarbon Blend	Hydrocarbon Blend
Open Time	20-30 Minutes	20-30 Minutes	20-30 Minutes	20-30 Minutes	20-30 Minutes
Tack Time	2-4 Minutes	2-4 Minutes	2-4 Minutes	2-4 Minutes	2-4 Minutes
Heat Resistance	Max Temp 160°F	Max Temp 160°F	Max Temp 160°F	Max Temp 160°F	Max Temp 160°F
Viscosity	5,000 cps #1 SPINDLE @10 RPM	5,000 cps #1 SPINDLE @10 RPM	5,000 cps #1 SPINDLE @10 RPM	5,000 cps #1 SPINDLE @10 RPM	5,000 cps #1 SPINDLE @10 RPM
Solids	25% +/- 1%	25% +/- 1%	25% +/- 1%	25% +/- 1%	25% +/- 1%
Spray Pattern	Web	Web	Web	Web	Web
VOC %	55% By Weight	228.11 g/l	228.11 g/l	228.11 g/l	228.11 g/l
VOC Compliant for CA & OTC	Yes	Yes	Yes	Yes	Yes
Aerosol Flammability Level	Level 3, Flammable	Level 3, Flammable	Level 3, Flammable	Level 3, Flammable	Level 3, Flammable
Warranty Period	One Year From Date of Shipment	One Year From Date of Shipment	One Year From Date of Shipment	One Year From Date of Shipment	One Year From Date of Shipment
DOT Proper Shipping Name	UN3161/Class 2.1 for domestic ground shipment. (See MSDS for additional shipping info)	UN3161/Class 2.1 for domestic ground shipment. (See MSDS for additional shipping info)	UN3161/Class 2.1 for domestic ground shipment. (See MSDS for additional shipping info)	UN3161/Class 2.1 for domestic ground shipment. (See MSDS for additional shipping info)	UN3161/Class 2.1 for domestic ground shipment. (See MSDS for additional shipping info)

Office: 678.494.1112 • Fax: 678.494.1113 • 313 Bell Park Drive • Woodstock, GA 30188

Where Quality and Service are Number 1

www.losorea.com • www.qualityaerosols.com