

Q6300 LPN PRESSURE SENSITIVE NON-FLAM PRODUCT DATA SHEET VOC COMPLIANT - ALL STATES*

Q6300 HIGH TEMPERATURE, HIGH SOLIDS NON-FLAMMABLE PRESSURE SENSITIVE SPRAY ADHESIVE is a fast tack, high shear adhesive. Q6300 is especially formulated for permanent or temporary bonding applications. Q6300 may also be used for making permanent or temporary bonds to other compatible non-porous or porous substrates. Q6300 is designed for applications requiring soft glue lines, and non-staining when applied in accordance with application instructions and has the ability to be re-positioned before bonding. It is recommended that all substrates be tested for compatibility with adhesive before using in production. Product should be used at room temperature or at least at 70°F.

Container Size	38# DOT 923-933-39 & TC -39M	177# TC #14761	355# TC 200 Gallon
Product Description	Canister Adhesive	Cylinder Adhesive	Cylinder Adhesive
Net Weight	34 lbs.	177 lbs.	355 lbs.
Weight Per Gallon	9.92	9.92	9.92
Can Per Case	1	1	1
Case Dimensions - Inches	12.50"L X 12.50" W X 18.00"H	16" diameter X 49" High	25" diameter X 42" High
Case Weight	47.0 Pounds	246.0 Pounds	502.00 Pounds
Cases Per Pallet	36	9	4
Appearance	Clear or Green	Clear or Green	Clear or Green
Odor	Solvent	Solvent	Solvent
Solvent System	Methylene Chloride	Methylene Chloride	Methylene Chloride
Propellant	1,1,1,2-Tetrafluoroethane	1,1,1,2-Tetrafluoroethane	1,1,1,2-Tetrafluoroethane
Open Time	15-20 Minutes	15-20 Minutes	15-20 Minutes
Tack Time	2-4 Minutes	2-4 Minutes	2-4 Minutes
Heat Resistance	Max Temp 180°F	Max Temp 180°F	Max Temp 180°F
Viscosity	8,000 cps #1 SPINDLE @10 RPM	8,000 cps #1 SPINDLE @10 RPM	8,000 cps #1 SPINDLE @10 RPM
Solids	25% +/- 1%	25% +/- 1%	25% +/- 1%
Spray Pattern	Web	Web	Web
VOC %	0 g/l	0 g/l	0 g/l
VOC Compliant for CA & OTC	*Yes	*Yes	*Yes
Aerosol Flammability Level	Non-Flammable	Non-Flammable	Non-Flammable
Warranty Period	One Year From Date of Shipment	One Year From Date of Shipment	One Year From Date of Shipment
DOT Proper Shipping Name	UN3159/Class 2.2 for domestic ground shipment. (See MSDS for additional shipping info)	UN3159/Class 2.2 for domestic ground shipment. (See MSDS for additional shipping info)	UN3159/Class 2.2 for domestic ground shipment. (See MSDS for additional shipping info)

* Not compliant in SCAQMD - Check AQ Regulations for other California District to determine compliance.

Office: 678.494.1112 • Fax: 678.494.1113 • 313 Bell Park Drive • Woodstock, GA 30188

Where Quality and Service are Number 1

www.losorea.com • www.qualityaerosols.com