

Q7500 LHT HIGH TACK ADHESIVE - FAST TACK - FAST DRY

PRODUCT DATA SHEET

NOT VOC COMPLIANT - CALIFORNIA AND OTC STATES

Q7500 HIGH SOLIDS, QUICK DRY PRESSURE SENSITIVE SPRAY ADHESIVE is a fast tack, with long open time and high shear. Q7500 is especially formulated for the manufactured housing and recreational vehicle industry for installing insulation in side walls and bonding expanded polystyrene foam (EPS) and other substrates to various substrates. Q7500 can be sprayed directly onto EPS surface without pitting or cavitating damage to the foam. Q7500 can be used for permanent or temporary lamination of ABS plastics, EPS, fabric, cork, fiberglass insulation to substrates such as wood, particle board, plywood, etc., and hot and cold insulated panel systems and many more applications. Product should be used at room temperature or at least at 70°F. For canister we recommend the Quality Aerosol "TBQ" spray tip.

Container Size	38# DOT 923-933-39 & TC -39M	177# TC #14761	355# TC 200 Gallon
Product Description	Canister Adhesive	Cylinder Adhesive	Cylinder Adhesive
Net Weight	28 lbs.	140 lbs.	270 lbs.
Weight Per Gallon	6.83	6.83	6.83
Can Per Case	1	1	1
Case Dimensions - Inches	12.50"L X 12.50" W X 18.00"H	16" diameter X 49" High	25" diameter X 42" High
Case Weight	42.0 Pounds	209.0 Pounds	417.00 Pounds
Cases Per Pallet	36	9	4
Appearance	Natural	Natural	Natural
Odor	Slight Solvent	Slight Solvent	Slight Solvent
Solvent System	Pentane, Acetone	Pentane, Acetone	Pentane, Acetone
Propellant	Dimethyl Ether	Dimethyl Ether	Dimethyl Ether
Open Time	5-10 Minutes	5-10 Minutes	5-10 Minutes
Tack Time	20-30 Seconds	20-30 Seconds	20-30 Seconds
Heat Resistance	Max Temp 160°F	Max Temp 160°F	Max Temp 160°F
Viscosity	8,000 cps #1 SPINDLE @10 RPM	8,000 cps #1 SPINDLE @10 RPM	8,000 cps #1 SPINDLE @10 RPM
Solids	40% +/- 2%	40% +/- 2%	40% +/- 2%
Spray Pattern	Web	Web	Web
VOC %	667.04 g/l	667.04 g/l	667.04 g/l
VOC Compliant for CA & OTC	No	No	No
Aerosol Flammability Level	Level 3, Flammable	Level 3, Flammable	Level 3, Flammable
Warranty Period	One Year From Date of Shipment	One Year From Date of Shipment	One Year From Date of Shipment
DOT Proper Shipping Name	UN3161/Class 2.1 for domestic ground shipment. (See MSDS for additional shipping info)	UN3161/Class 2.1 for domestic ground shipment. (See MSDS for additional shipping info)	UN3161/Class 2.1 for domestic ground shipment. (See MSDS for additional shipping info)

Office: 678.494.1112 • Fax: 678.494.1113 • 313 Bell Park Drive • Woodstock, GA 30188

Where Quality and Service are Number 1

www.losorea.com • www.qualityaerosols.com