

**Q7750 TANK INSULATION ADHESIVE FLAMMABLE - SPRAY GRADE
 PRODUCT DATA SHEET**

VOC COMPLIANT - CALIFORNIA AND OTC STATES

Q7750 TANK INSULATION ADHESIVE FLAMMABLE - SPRAY GRADE is a high quality VOC Compliant fast-drying quick setting contact adhesive designed to produce a strong permanent bond used with a variety of porous and non-porous substrates, such as rubber, foam, metal, wood, particleboard, cloth. An excellent product for bonding flexible closed cell EPDM Elastomeric Sheet Insulation on many types of piping systems, equipment and tanks. For insulation of HVAC ducting systems, including supply, return and intake air. Product is used as a contact adhesive which requires both surfaces to be coated with adhesive, wait approximately 5 minutes before mating coated surfaces. Product can be sprayed, brushed or rolled.

Container Size	5 Gallon Pail	55 Gallon Drum
Product Description	Bulk Adhesive	Bulk Adhesive
Net Weight	35 Pounds	395 Pounds
Weight Per Gallon	7.22	7.22
Pails/Drums Per Pallet	36	4
Appearance	Amber	Amber
Odor	Pungent	Pungent
Solvent System	Esters/Aliphatic	Esters/Aliphatic
Open Time	5-10 Minutes	5-10 Minutes
Tack Time	5 Minutes	5 Minutes
Heat Resistance	Max Temp 160°F	Max Temp 160°F
Viscosity	100 cps #1 SPINDLE @10 RPM	100 cps #1 SPINDLE @10 RPM
Solids	28% +/- 2%	28% +/- 2%
Spray Pattern	Mist	Mist
VOC Grams per Liter	246 g/l	246 g/l
VOC Compliant for CA & OTC	Yes	Yes
Flammability Level	Level 3, Flammable	Level 3, Flammable
Warranty Period	One Year From Date of Shipment	One Year From Date of Shipment
DOT Proper Shipping Name	UN1133/Class 3 domestic ground shipment. (See MSDS for additional shipping info)	UN1133/Class 3 domestic ground shipment. (See MSDS for additional shipping info)

Office: 678.494.1112 • Fax: 678.494.1113 • 313 Bell Park Drive • Woodstock, GA 30188

Where Quality and Service are Number 1

www.losorea.com • www.qualityaerosols.com