

Q7850 WHITE WOOD GLUE
PRODUCT DATA SHEET
VOC COMPLIANT - ALL STATES

Q7850 WHITE WOOD GLUE is a fast setting polyvinyl acetate ethylene emulsion adhesive that is designed for woodworking application including wood joints, and in press machines for high pressure laminates. Q7850 may also be applied using a brush, roller, spreader and may be sprayed.

Container Size	5 Gallon Pail	55 Gallon Drum	250 Gallon Tote Tank
Product Description	Bulk Adhesive	Bulk Adhesive	Bulk Adhesive
Net Weight	43 Pounds	475 Pounds	2500 Pounds
Weight Per Gallon	8.6	8.6	8.6
Containers Per Pallet	36	4	1
Appearance	White	White	White
Odor	Slight	Slight	Slight
Solvent System	Polyvinyl Acetate Ethylene	Polyvinyl Acetate Ethylene	Polyvinyl Acetate Ethylene
Propellant	N/A	N/A	N/A
Open Time	20-30 Minutes	20-30 Minutes	20-30 Minutes
Tack Time	2-5 Minutes	2-5 Minutes	2-5 Minutes
Heat Resistance	160°F Plus	160°F Plus	160°F Plus
Viscosity	6,000 cps #1 SPINDLE @10 RPM	6,000 cps #1 SPINDLE @10 RPM	6,000 cps #1 SPINDLE @10 RPM
Solids	47-51%	47-51%	47-51%
Spray Pattern	N/A	N/A	N/A
VOC %	0 g/l	0 g/l	0 g/l
VOC Compliant for CA & OTC	Yes	Yes	Yes
Aerosol Flammability Level	Class 3	Class 3	Class 3
Warranty Period	One Year From Date of Shipment	One Year From Date of Shipment	One Year From Date of Shipment
DOT Proper Shipping Name	UN1133/CLASS 3 domestic ground shipment. (See MSDS for additional shipping info)	UN1133/CLASS 3 domestic ground shipment. (See MSDS for additional shipping info)	UN/1133/CLASS 3 domestic ground shipment. (See MSDS for additional shipping info)

Office: 678.494.1112 • Fax: 678.494.1113 • 313 Bell Park Drive • Woodstock, GA 30188

Where Quality and Service are Number 1

www.losorea.com • www.qualityaerosols.com