

Q7950 Yellow Wood Glue PRODUCT DATA SHEET VOC COMPLIANT - ALL STATES

Q7950 YELLOW WOOD GLUE is a fast setting polyvinyl acetate ethylene adhesive that is designed for woodworking applications including wood joints and in press machines for high pressure laminate. Q7950 may also be applied using a brush, roller, sprayer and may be sprayed.

Container Size	5 Gallon Pail	55 Gallon Drum	250 Gallon Tote Tank
Product Description	Bulk Adhesive	Bulk Adhesive	Bulk Adhesive
Net Weight	43 Pounds	475 Pounds	2500 Pounds
Weight Per Gallon	8.6	8.6	8.6
Containers Per Pallet	36	4	1
Appearance	Yellow	Yellow	Yellow
Odor	Slight	Slight	Slight
Solvent System	Emulsion	Emulsion	Emulsion
Propellant	N/A	N/A	N/A
Open Time	20-30 Minutes	20-30 Minutes	20-30 Minutes
Tack Time	2-5 Minutes	2-5 Minutes	2-5 Minutes
Heat Resistance	160°F +	160°F +	160°F +
Viscosity	6,000 cps #1 SPINDLE @10 RPM	6,000 cps #1 SPINDLE @10 RPM	6,000 cps #1 SPINDLE @10 RPM
Solids	47-51%	47-51%	47-51%
Spray Pattern	N/A	N/A	N/A
VOC %	0 g/l	0 g/l	0 g/l
VOC Compliant for CA & OTC	Yes	Yes	Yes
Aerosol Flammability Level	Class 3	Class 3	Class 3
Warranty Period	One Year From Date of Shipment	One Year From Date of Shipment	One Year From Date of Shipment
DOT Proper Shipping Name	UN1133/CLASS 3 domestic ground shipment. (See MSDS for additional shipping info)	UN1133/CLASS 3 domestic ground shipment. (See MSDS for additional shipping info)	UN/1133/CLASS 3 domestic ground shipment. (See MSDS for additional shipping info)

Office: 678.494.1112 • Fax: 678.494.1113 • 313 Bell Park Drive • Woodstock, GA 30188

Where Quality and Service are Number 1

www.losorea.com • www.qualityaerosols.com